

 L&L Products<sup>®</sup>

The background of the advertisement features a large, abstract geometric shape composed of several overlapping triangles in shades of red and grey. A white square is positioned on the right side of the grey area, with a thin white line extending downwards from its bottom-left corner towards the text below.

BEYOND LIMITS

**T<sup>LINK</sup>** LINK<sup>®</sup>

An advanced engineering thermoplastic adhesive  
for ultimate performance and processability.

[lproducts.com/t-link](https://lproducts.com/t-link)

# T-LINK® SELECTION GUIDE

FORM	PRODUCT	Melt Index g/min @ 190°C	GRADES	AVAILABILITY	WHAT DOES IT ENABLE
PELLETS	PELLETS (L-TE01)	10	Approx. 3 mm pellet size	Commercially Available	<ul style="list-style-type: none"> <li>- Can be used as a base resin or modifier in formulated products</li> <li>- Can be used in compression molding, injection molding, and overmolding</li> </ul>
		10	600–800 µm	Commercially Available	<ul style="list-style-type: none"> <li>- Precise areal weight loading of resin on fabrics and composites</li> <li>- Modifier in formulated products</li> </ul>
FILM	FILM (L-F610)	10	2.5 mil [63 µm] thickness	Commercially Available	<ul style="list-style-type: none"> <li>- Dry, easy-to-handle product</li> </ul>
		10	5 mil [127 µm] thickness	Commercially Available	<ul style="list-style-type: none"> <li>- Provides consistent and efficient delivery of resin system for composite manufacturing</li> </ul>
YARN/ FILAMENTS	COATED ARAMID YARN*		3360 dTex aramid fiber is coated with T-Link® to 5250 dTex	Commercially Available	<ul style="list-style-type: none"> <li>- Can be co-woven with reinforcement fibers</li> <li>- Creates a drapable fabric with a very consistent and precise resin content that is ready for consolidation</li> </ul>
			450, 850 or 2400 dTex	Developmental Technology	<ul style="list-style-type: none"> <li>- Can be used in weaving, knitting, and braiding</li> </ul>

\*Converted form



Scan for disclaimer